



SPRAY U 951 AUTO FLEX UNDERBODY

Technical Data Sheet No 824

General Technical Description

A combination of caoutchouc / synthetic resin which has excellent adhesion

It can be painted over immediately wet on wet using synthetic paints or with one or two component acrylic paints, after drying (or 20-30 min the latest)

Remains permanently elastic

Fast drying

VOC compliant with the regulations

Surface

Inside bottom parts of the car body

Outside bottom parts of the car body

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER

Make sure the surface is air dried rather than wiped dry

Product Application: Apply on the inside and outside bottom parts of the car body.



Shake well before using

Flash Point:
-97°C (-206°F)

Remarks:

- Always try to use the product in accordance with the specifications provided.
- It can be used by countries that do not adopt the VOC legislation as well.
- Shake thoroughly before use.
- Shake for 2 -3 min after agitator ball has started to rattle. After preparing the area to be painted ensure it to be free from dirt, wax, oil etc.
- It is recommended to test on a similar surface for achieving the desired finishing effect.
- Optimum operating temperature range 10-25 °C (50 - 75°F).

Storage shelf life:

Store in a cool place +5 to +25 °C (41°F - 77°F) and use within 36 months for best results.



2-3 coats approximately 20-30 microns

Specific Gravity:
0.99 g/cm³

Solid Content (No thinner):
22% Weight



Spray at a distance of 20- 30 cm thinly applied coats build up within 5-10 minutes intervals will achieve best results.

VOC (2001/42/EC)
This product is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 650g/L.
2004/42/IIIB(e)(840)650



Dust free 10-15 mins at 23°C (73°F)
Through drying 4-5 hours

Theoretical Coverage:

-
Cleaning of equipment:
-



Make sure you always use appropriate face protection and good ventilation

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 5 / 2021, February 2021